

# 【定格総荷重表】



■9.5m～30.5mブーム

作業半径 (m)	(6.3m)				(5.1m)				(3.8m)				(2.2m)				作業半径 (m)		
	アウトリガ最大張出(全周)				アウトリガ中間(5.1m)張出(側方)				アウトリガ中間(3.8m)張出(側方)				アウトリガ最縮小張出(側方)						
	9.5mブーム	16.5mブーム	23.5mブーム	30.5mブーム	9.5mブーム	16.5mブーム	23.5mブーム	30.5mブーム	9.5mブーム	16.5mブーム	23.5mブーム	30.5mブーム	9.5mブーム	16.5mブーム	23.5mブーム	30.5mブーム			
2.5	25.00	18.00			25.00	18.00			25.00	18.00			12.00	11.60			2.5		
3.0	25.00	18.00	12.50		25.00	18.00	12.50		25.00	18.00	12.50		12.00	11.60	9.70		3.0		
3.5	25.00	18.00	12.50		25.00	18.00	12.50		20.00	18.00	12.50		9.35	8.95	9.70		3.5		
4.0	23.00	18.00	12.50	7.00	23.00	18.00	12.50	7.00	15.70	15.60	12.50	7.00	7.55	7.15	7.80	5.50	4.0		
4.5	21.20	18.00	12.50	7.00	21.20	18.00	12.50	7.00	12.60	12.60	12.50	7.00	6.20	5.80	6.45	5.50	4.5		
5.0	19.40	16.70	12.50	7.00	18.40	16.70	12.50	7.00	10.60	10.40	10.70	7.00	5.15	4.80	5.40	5.50	5.0		
5.5	17.80	15.50	11.75	7.00	15.40	15.00	11.75	7.00	9.05	8.80	9.30	7.00	4.35	4.00	4.60	4.75	5.5		
6.0	16.30	14.40	11.10	7.00	13.00	12.60	11.10	7.00	7.70	7.60	8.20	7.00	3.70	3.40	3.95	4.15	6.0		
6.5	15.10	13.45	10.40	7.00	11.20	10.80	10.40	7.00	6.60	6.50	7.25	7.00	3.15	2.85	3.40	3.65	6.5		
7.0		12.65	9.80	7.00		9.40	9.80	7.00		5.60	6.40	6.55		2.40	2.95	3.20	7.0		
7.5		11.90	9.25	7.00		8.25	8.90	7.00		4.90	5.70	5.90		2.05	2.55	2.80	7.5		
8.0		10.55	8.75	6.75		7.30	8.00	6.75		4.40	5.05	5.30		1.70	2.25	2.50	8.0		
9.0		8.40	7.85	6.15		5.80	6.50	6.15		3.50	4.05	4.35		1.10	1.75	1.95	9.0		
10.0		6.90	7.10	5.60		4.70	5.40	5.60		2.80	3.30	3.65		0.65	1.35	1.55	10.0		
11.0		5.70	6.40	5.15		3.90	4.55	4.80		2.15	2.75	3.05			0.95	1.20	11.0		
12.0		4.80	5.45	4.70		3.25	3.85	4.15		1.65	2.30	2.60				0.90	12.0		
13.0		4.10	4.70	4.35		2.70	3.25	3.55		1.30	1.90	2.20					13.0		
13.5		3.80	4.40	4.20		2.50	3.05	3.30		1.10	1.75	2.00					13.5		
14.0			4.10	4.05			2.85	3.10			1.55	1.85					14.0		
15.0			3.60	3.80			2.45	2.70			1.30	1.55					15.0		
15.5			3.40	3.65			2.25	2.50			1.15	1.45					15.5		
16.0			3.15	3.45			2.10	2.35			1.00	1.30					16.0		
17.0			2.80	3.05			1.80	2.10			0.75	1.10					17.0		
18.0			2.45	2.70			1.50	1.80			0.55	0.90					18.0		
19.0			2.15	2.45			1.25	1.60			0.40	0.70					19.0		
20.0			1.90	2.20			1.05	1.40				0.55					20.0		
20.5			1.80	2.05				1.30									20.5		
21.0				1.95				1.20									21.0		
22.0				1.75				1.00									22.0		
24.0				1.40				0.70									24.0		
26.0				1.15				0.45									26.0		
27.5				0.95													27.5		
危険角度	—	—	—	—	—	—	—	—	—	—	—	—	20°	40°	—	40°	53°	60°	危険角度

(単位: ton)

■アウトリガ不使用時

作業半径 (m)	定 置 つ り						走 行 つ り (2km/h未満)						作業半径 (m)		
	9.5mブーム		16.5mブーム		23.5mブーム		9.5mブーム		16.5mブーム		23.5mブーム				
	前方	全周	前方	全周	前方	全周	前方	全周	前方	全周	前方	全周			
3.0	14.00	9.00	9.00	7.30			10.50	7.00	7.50	5.10			3.0		
3.5	14.00	7.60	9.00	7.30	6.50	4.50	10.50	6.20	7.50	5.10	5.50	3.20	3.5		
4.0	12.50	6.30	9.00	5.85	6.50	4.50	9.50	5.30	7.50	4.90	5.50	3.20	4.0		
4.5	10.90	5.20	9.00	4.75	6.50	4.50	8.70	4.40	7.50	3.95	5.50	3.20	4.5		
5.0	9.55	4.30	8.20	4.00	6.50	4.30	7.70	3.60	7.00	3.30	5.50	3.20	5.0		
5.5	8.30	3.60	7.40	3.30	6.05	3.70	6.80	3.00	6.20	2.70	5.15	3.10	5.5		
6.0	7.20	3.00	6.60	2.80	5.65	3.20	5.90	2.50	5.50	2.30	4.80	2.70	6.0		
6.5	6.25	2.50	5.90	2.35	5.25	2.75	5.10	2.10	4.90	1.90	4.45	2.30	6.5		
7.0			5.25	1.95	4.85	2.40			4.35	1.60	4.15	2.00	7.0		
8.0			4.10	1.35	4.10	1.80			3.40	1.00	3.50	1.50	8.0		
9.0			3.25	0.85	3.50	1.40			2.70	0.60	2.95	1.10	9.0		
10.0			2.60	0.45	3.00	1.05			2.10		2.45	0.75	10.0		
11.0			2.10		2.55	0.75			1.65		2.05	0.55	11.0		
12.0			1.70		2.20				1.30		1.70		12.0		
13.0			1.35		1.85				1.00		1.40		13.0		
14.0					1.50						1.15		14.0		
15.0					1.25						0.95		15.0		
16.0					1.00						0.75		16.0		
17.0					0.80						0.60		17.0		
18.0					0.60								18.0		
危険角度	—	—	—	—	40°	—	53°	—	—	—	—	45°	30°	54°	危険角度

(単位: ton)