

**TOTAL RATED LOADS**

(1) With outriggers set  
[BOOM]

Unit: ton

Outriggers fully extended (6.7m) -360°→					
B \ A	9.5m	16.2m	22.9m	29.6m	36.3m
3.0m	35.0	22.5	14.0		
3.5m	30.6	22.5	14.0	10.0	
4.0m	27.5	22.5	14.0	10.0	
4.5m	24.7	20.7	14.0	10.0	7.0
5.0m	22.3	19.3	14.0	10.0	7.0
5.5m	20.3	17.9	14.0	10.0	7.0
6.0m	18.6	16.8	13.4	10.0	7.0
6.5m	16.4	15.8	12.5	10.0	7.0
7.0m	14.5	14.9	11.8	10.0	7.0
8.0m		13.1	10.6	8.9	7.0
9.0m		10.7	9.6	8.0	6.3
10.0m		9.0	8.6	7.2	5.8
11.0m		7.4	7.7	6.55	5.3
12.0m		6.1	6.7	6.0	4.9
13.0m		5.1	5.85	5.55	4.5
14.0m			5.1	5.1	4.15
15.0m			4.4	4.6	3.85
16.0m			3.8	4.15	3.6
17.0m			3.3	3.75	3.35
18.0m			2.9	3.3	3.15
19.0m			2.5	2.95	2.95
20.0m			2.2	2.6	2.7
22.0m				2.0	2.2
24.0m				1.5	1.75
26.0m				1.1	1.35
28.0m					1.0
30.0m					0.75
32.0m					0.55
33.0m					0.45
a (°)	0° 83				

Unit: ton

Outriggers middle extended (6.3m) -Over sides-					
B \ A	9.5m	16.2m	22.9m	29.6m	36.3m
3.0m	35.0	22.5	14.0		
3.5m	30.6	22.5	14.0	10.0	
4.0m	27.5	22.5	14.0	10.0	
4.5m	24.7	20.7	14.0	10.0	7.0
5.0m	22.3	19.3	14.0	10.0	7.0
5.5m	20.3	17.9	14.0	10.0	7.0
6.0m	18.6	16.8	13.4	10.0	7.0
6.5m	16.4	15.8	12.5	10.0	7.0
7.0m	14.5	14.9	11.8	10.0	7.0
8.0m		12.6	10.6	8.9	7.0
9.0m		10.0	9.6	8.0	6.3
10.0m		8.0	8.6	7.2	5.8
11.0m		6.6	7.4	6.55	5.3
12.0m		5.4	6.25	6.0	4.9
13.0m		4.5	5.3	5.55	4.5
14.0m			4.6	4.8	4.15
15.0m			3.95	4.3	3.85
16.0m			3.4	3.8	3.6
17.0m			2.9	3.35	3.35
18.0m			* 2.55	2.95	3.1
19.0m			' 2.15	2.55	2.75
20.0m			1.85	2.25	2.45
22.0m				1.7	1.95
24.0m				1.3	1.5
26.0m				0.9	1.15
28.0m					0.8
30.0m					0.55
a (°)	0° 83				20° 83

A= Boom length B= Working radius  
a= Boom angle range (for the unladen condition)